

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2001-342451

(43)Date of publication of application : 14.12.2001

(51)Int.Cl.

C09K 3/00
A61K 7/00
A61K 7/032
A61K 7/11
A61K 7/13
A61K 7/48
C08J 3/075
C08J 3/12
C08L 5/00
C08L 89/00
C08L101/00

(21)Application number : 2001-003875

(71)Applicant : SHISEIDO CO LTD

(22)Date of filing : 11.01.2001

(72)Inventor : MIYAZAWA KAZUYUKI
NAKAMURA TADASHI
KANEDA ISAMU
HARIKI TOSHIO

(30)Priority

Priority number : 2000002610
2000094307

Priority date : 11.01.2000
30.03.2000

Priority country : JP
JP

(54) METHOD FOR MANUFACTURING THICKENER AND COSMETIC

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a new-type thickener giving no sticking feeling nor squeaky feeling, having excellent handleability, free from causing viscosity loss even in the case where it is highly compounded with a water-soluble drug component or slat, and stale for a long period so that a phenomenon such as water separation does not occur.

SOLUTION: A method for manufacturing the thickener by dissolving a hydrophilic compound having gelling ability, or a hydrophilic compound having gelling ability and a thickening compound having no gelling ability in water or an aqueous component, subsequently leaving the resulting solution for cooling to form gel, and then pulverizing the gel into microgel having an average particle size of 0.1-1,000 μm to prepare the thickener. The thickener obtained by the method, and a cosmetic containing the thickener.